




 Specification


Model		AH3800CG010E
Basic	Sensor	IMX678
	Image Sensor	1/1.8"CMOS
	Shutter	Rolling
	Resolution	3840 × 2160
	Frame Rate	14.5 fps
	Bit Depth	12
	Mono/Color	Color
	Pixel Size	2.0 μm × 2.0 μm
Image	Pixel	8 MP
	S/N Ratio	39.7 dB
	Dynamic Range	66.5 dB
	Image Format	Mono8,BayerRG8/10/10Packed/12/12Packed,YUV422_8_UYVY,YUV422_8
	Binning	Support
	ROI	Support
	Gain	0 ~ 72 dB
	White Balance	Support
	Gamma	From 0 to 4, support LUT
	Exposure Time	16 μs ~ 1 s
	Trigger Mode	Software Trigger/Hardware Trigger/Free Run Mode
	SPC	Support
Performance	User Setting	Support three sets of user-defined configurations
	Image Buffer	256MB
Port	Port	GigE, PoE
	GPIO Interface	1× 6 pin Hirose: 1× Opto-isolated input, 1× Opto-isolated output, 1 configurable input and output
	Lens Mount	C-mount
Power	Power Supply	PoE/ DC 9V~24V power supply via Hirose interface
	Power Consumption	12 V≈3.8 W
Structure	Product Dimensions	29 mm × 29 mm × 42 mm (not including lens mount and rear case connector)
	Net Weight	94 g
Environment	Storage Temperature	-30℃~+80℃
	Operating Temperature	0℃~+50℃

Connector Pin-out

Definitions of camera 6-pin ports:

Pin	Description	Features
1	-	+9VDC to 24VDC power supply
2	Line1	Opto-isolated input
3	Line2	GPIO (I/O can be configured for non-isolated software) ¹
4	Lineo	Opto-isolated output
5	-	Opto-isolated signal ground (ISO_GND)
6	-	Camera DC power ground and GPIO signal ground (GND)

Definition of 6-pin power port



Spectrogram

