5000 series


L5087CT370E



Features

- 10GigE interface, provides up to 10Gbps effective bandwidth;
- Supports external trigger, free run mode and multiple modes;
- Supports Gamma correction, LUT and other ISP functions;
- Conform to GigE Vision protocol and GenICam standard;
- Applies DC 24V power supply;
- Comply with CE, UL, RoHS certifications;
- True color RGB mode .

Dimensions (mm)





Specification

Model		L5087CT370E		
Basic	Sensor	8K		
	Image Sensor	CMOS		
	Shutter	Global		
	Resolution	8192 × 3		
	Line Rate	48 kHz		
	Bit Depth	12		
	Mono/Color	Color		
	Pixel Size	7 μm × 7 μm		
	Pixel	8192 × 3		
	S/N Ratio	40 dB		
	Dynamic Range	63.3 dB		
	Image Format	RGB8		
	Binning	Support		
Trace	ROI	Support		
Image	X Flip	Support		
	Gain	1~32		
	Gamma	From 0 to 4, support LUT		
	Exposure Time	4μS~100mS		
	Trigger Mode	Software Trigger/Hardware Trigger/Free Run Mode		
	FPN	Support		
Performance	User Setting	Support two sets of user-defined configurations		
Port	Port	10Gige		
	GPIO Interface	4 differential input, output, and 1 GPIO input, output,		
	Lens Mount	M72		
Dower	Power Supply	DC 12~24V power supply via 12-pin Hirose connector		
Power	Power Consumption	14W		
Structure	Product Dimensions	80mm×80mm×48.2mm(Not including rear case connector)		
	Net Weight	520 g		
Environment	Storage Temperature	-30°C~+80°C		
	Operating Temperature	0°C ~ +50°C		



Connector Pin-out

Color	Pin	Signal	Input/output	Specifications	
				Differential mode	Single-ended mode
	1	GND	-	Power GND	
	2	VIN	-	Camera Power Supply	
	3	LINE1+	Input/output	Configurable Input/output	Configurable Input/output
	4	LINE1-	Input/output	Configurable Input/output	Suspended (not connected)
	5	GND	-	Signal GND	
	6	LINE2+	Input/output	Configurable Input/output	Configurable Input/output
	7	LINE2-	Input/output	Configurable Input/output	Suspended (not connected)
	8	GPIO	Input/output	non-isolated configurable I/O	
	9	LINE3+	Input/output	Configurable Input/output	Configurable Input/output
	10	LINE3-	Input/output	Configurable Input/output	Suspended (not connected)
	11	LINE4+	Input/output	Configurable Input/output	Configurable Input/output
	12	LINE4-	Input/output	Configurable Input/output	Suspended (not connected)
	Shell	Shield GND	Shell	Connected to the encoder shield	

Spectrogram

